

2008 Ultimate 20 North Americans Huntington Lake , CA – July 20–23, 2008 Sail Measurement & Boat Inspection Form

All boats must meet the current Ultimate 20 One-Design Class Rules. This inspection shall not prevent the challenge of any boat entered to prove that all of the other requirements of the U20 One-Design Rules have been met. **You or your representative must be present while your boat is inspected**. Please present this form to the sail measurer and to your boat inspector. It will be collected after all items are completed.

Hull # ______ Sail No. _____Owner/Skipper: _____

Hull Weight:

Weight: The dry weight of the boat shall not be less than 1,100 lbs. This weight shall include the keel, keel lifting crane assembly, bowsprit and its housing and retracting line, jib roller furling drum, traveler, rudder bracket, companionway hatch covers, and foredeck hatch assembly, if so equipped.

The total weight of the boat, ready to race, shall not be less than 1,250 lbs., including the above, plus rudder and tiller assembly, mast, boom, all standing and running rigging, blocks and cleats, stanchions and lifelines, sheet bags, compass and running lights. Excluding sails, dock lines, fenders, batteries, cushions, lifesaving equipment and other required equipment specified in Rules OD-VI and OD-VII.

<u>Mast Rake</u>: The total length of the headstay assembly must be such that the rake of the mast is between 34'-9" and 35'.

Sail Measurement:

Mainsail measured and passed. Jib measured and passed. Jib measured and passed. Spinnaker measured and passed.

Required Safety Equipment: The following items are required:

Type I, II or III PFD's for everyone on board One Type IV or V throwable PFD Whistle or horn. One Type B1 fire extinguisher. Paddle not less than 48 inches long. Anchor, with or without chain, of combined minimum weight of 5 lbs., and a minimum of 100 ft., of 3/8" non-floating rode. Bailing device: 2-gallon bucket and/or manual pump. Marine first-aid kit. **Other Required Equipment:** The following items are required on board while racing:

Companionway hatches.

Keel crane and post

Outboard motor of at least 2 hp, motor bracket, and a minimum of $\frac{1}{2}$ gallon of fuel **or** penalty weight of 30 lbs., secured to the interior mast support.

Two fenders.

One Marine Compass of any type.

Appropriate dock lines.

< 2" slack in lifelines (midpoint of lifeline must be no more than 2 inches lower than at attachment point under no load).

Declared Crew Weight:

Weight		Name	
	Driver		
	Crew #1		-
	_ Crew #2		-
	_ Total (must b	be <614 lbs.)	
Inspected b	<u> </u>		
Printed Nam	1e		
Signature _			
-			
Date:			