## 2006 Ultimate 20 North American Championship June 22 – 25, 2006 Cascade Locks, Oregon Sail Measurement & Boat Inspection Form

All boats must meet the current Ultimate 20 One-Design Class Rules. This inspection shall not prevent the challenge of any boat entered to prove that all of the other requirements of the U20 One-design Rules have been met. You or your representative must be present while your boat is inspected. Please present this form to the sail measurer and to your boat inspector. It will be collected after all items are complete.

Hull #\_\_\_\_\_ Sail # \_\_\_\_\_ Owner/Skipper \_\_\_\_\_

## Hull Weight:

**Weight**: The dry weight of the boat shall not be less than 1,100 lbs. This weight shall include the keel, keel lifting crane assembly, bowsprit and its housing and retracting line, jib roller furling drum, traveler, rudder bracket, companionway hatch covers, and foredeck hatch assembly, if so equipped.

**The total weight of the boat**, ready to race, shall not be less than 1250 lbs., including the above, plus rudder and tiller assembly, mast, boom, all standing and running rigging, blocks and cleats, stanchions, and lifelines, sheet bags, compass and running lights. Excluding sails, dock lines, fenders, batteries, cushions, lifesaving equipment and other required equipment specified in Rules OD-VI and OD-VII.

<u>Mast Rake</u>: The total length of the head stay assembly must be such that the rake of the mast is between 34'-9" and 35'. As measured: \_\_\_\_\_\_

## Sail Measurements: (Measurer's Initials required)

\_\_\_\_\_ Mainsail measured and passed.

\_\_\_\_\_ Jib Measured and passed.

\_\_\_\_\_ Spinnaker measured and passed.

Required Safety Equipment: The following items are required to be on board while racing:

- Type I, II or III PFD's for everyone on board.
- One Type IV or V throw able PFD.
- Whistle or horn.
- One Type B1 fire extinguisher.
- Paddle not less than 48 inches long.
- Anchor, with or without chain, of combined minimum weight of 5 lbs., and a minimum of 100 ft. of 3/8" non-floating rode.
- Bailing device: 2-gallon bucket and/or manual pump.
- Marine first-aid kit.

**<u>Other Required Equipment</u>**: The following items are required on board while racing:

- Companionway hatches.
- Companionway floor boards or approved covering.
- Keel crane and post.
- Outboard motor of at least 2 hp, motor bracket, and minimum of ½ gallon of fuel **or** penalty weight of 30 lbs., secured to the interior mast support.
- Two fenders.
- One Marine Compass of any type.
- Appropriate dock lines.
- <2" slack in lifelines (midpoint of lifeline must be no more than 2 inches lower than at the attachment point under no load.)

## Inspected by:

Printed Name	
Signature	Date: _